

LV2600 2nd Life BATTERY MODULE



The LV2600 2nd Life is a high-performance, scalable battery storage module. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

- 
Low Voltage
- 
Easy Installation
- 
High Efficiency
- 
Expandable System
- 
90% DoD

Additional batteries can be installed in parallel. With a plug and play solution that can save valuable time for installers.



LOW VOLTAGE BATTERIES FROM SOLARBOX, MORE AT>>

solarbox.es



SPECIFICATIONS

Nominal Voltage (V)	51.2
Nominal Capacity (Wh)	2560
Usable Capacity (Wh)	2400
Discharge Voltage (v)	43.2-57.6
Recommend Discharge Current (A)	25
Max.Charge / Discharge Current (A)	50
Peak Discharge Current (A)	100@15sec
Communication	CAN RS485
Working Temperature	0-55°C charge / -20 -55 °C discharge
Shelf Temperature	-20 -60°C
Protective Class	IP21
Cooling type	Natural Cooling
Humidity	5% --- 85%
Certification	CE
Cycle Life	>6000 25 C (25 C/ 77 F)
Dimensions (L* W* H) (mm)	440 (L) * 440 (W) * 116 (H)
Reference to standards	IEC6219, IEC62040, IEC62477-1, VDE251-50, UN38.3